EC799 ELECTRONIC CALIPERS 0-40"/0-1000MM



METROLOGY SOLUTIONS

The EC799 Electronic Caliper is light, comfortable, easy-to-use, and constructed with features that have made Starrett slide calipers the machinist's first choice for many years. Output now available.

The EC799 offers a slim, streamlined profile, a large, clear, easy-to-read LCD display, long battery life, and function buttons for zero and inch/mm.

EC799 Electronic Slide Calipers				
Range				
Inches	mm	Cat. No.	EDP	
0-6	0-150	EC799A-6/150	00142	
		EC799A-6/150 W/SLC*	72665	
		EC799B-6/150	00143	
		EC799B-6/150 W/SLC*	00144	
0-8	0-200	EC799A-8/200	00145	
		EC799A-8/200 W/SLC*	72674	
		EC799B-8/200	00146	
		EC799B-8/200 W/SLC*	00147	
0-12	0-300	EC799A-12/300	00148	
		EC799A-12/300 W/SLC*	72673	
		EC799B-12/300	00149	
		EC799B-12/300 W/SLC*	00150	
799 Extended Slide Calipers				
0-24	0-600	799AZ-24/600	11978	
0-40	0-1000	799AZ-40/1000	11979	
Accessories and Case Information for 799 Electronic Calipers				

Cat. No.

PT26151

PT22431

PT99492

950

723ZZ-6/722ZZ-6

EDP

64440

64640

65650

57070

63878

56695

Finished wood case for U-12" (300mm) calipers	946
* Includes redemption card for Standard Letter of Certificatio	n (SLC).

Depth attachment for 6", 9" and 150mm calipers

Deluxe padded case for 0-6" (150mm) calipers

Finished wood case for 0-8" (200mm) calipers

FEATURES

- Lightweight, ergonomic design
- Inch/millimeter conversion reads .0005" or 0.01mm
- Easy access to the single, long-life battery
- · Last measuring position retained when shut off
- · Hardened stainless steel body for long life
- · Fine adjustment thumb wheel
- · Lock screw to hold the slide in position
- Resolution is .0005" (0.01mm)
- Zero at any position
- Protective case

6", 8" AND 12" CALIPERS ONLY

- · Large easy-to-read LCD, .32" high characters
- Automatic shut-off after 5 minutes of non-use
- Linear accuracy meets DIN862
- · Integrated depth rod

EXTENDED RANGE 24" AND 40" CALIPERS

- · Preset and hold feature
- . Minimum and maximum limits set
- 0.D. jaw dimension is 0.800"/20.32mm
- · LCD characters are .50" high
- · Auto shut-off after 30 minutes of non-use



Description

Center distance attachment

3-volt battery; CR2032

Outside Measurement





Depth Measurement



Step Measurement

Starrett





